

# FORMULATIONS FOR EXACTING STANDARDS

## HIGH-PERFORMANCE GREASE DESIGNED FOR SPECIFIC APPLICATIONS

Fersa grease is designed for outstanding performance in even the most demanding of situations.

Our wide variety of greases cover all your needs, from generic applications to specific greases designed for wheels of heavy vehicles.



## Fersa Grease Advantages

- Resistant to temperatures of up to 160 °C.
- Improved composition to ensure excellent lubrication.
- Strong adherence due to the plastic deformation of micro additives.
- Rust-proof and resistant to vibration.



### HI-TEMP PRO 3

Resistant to high temperatures, especially formulated for automotive applications



### SPECIAL WHEEL END

Especially formulated for industrial vehicle wheel applications



### MULTIPURPOSE 2

Lithium grease designed for general applications. It protects against the development of fretting corrosion and premature wear of the bearing



### MULTIPURPOSE 3

	HI-TEMP PRO 3	SPECIAL WHEEL END	MULTIPURPOSE 2	MULTIPURPOSE 3
Available formats	0.5 kg / 1 kg	0.5 kg / 1 kg	0.5 kg / 1 kg	0.5 kg / 1 kg
Type of thickener	Complex lithium	Complex lithium	Lithium	Lithium
Dropping point	> 220	> 250	> 185	> 185
NLGI consistency number	3	2-3	2	3
Oil viscosity (cSt at 40 °C)	150 - 220	150	100 - 150	100 - 150
Welding load Four-ball EP test (kg)	> 200	> 250	> 200	> 200
Colour	Blue	Blue	Amber	Amber
Operating temperature	-30 / +160 °C -22 / +320 °F	-20 / +160 °C -4 / +320 °F	-20 / +120 °C -4 / +248 °F	-20 / +120 °C -4 / +248 °F